


Katalogový list

platný od: 1/1/22

+GF+

TITAN
METALPLAST



Otočná příruba PP - ocel pro svařování na tupo

- Rozteč děr dle PN 10
- Materiál: PP (30% skelného vlákna) s ocelovou vložkou
- Připojovací rozměry dle ISO 7005, EN 1092, BS 4504, DIN 2501
- AL: počet děr

d (mm)	DN (mm)	PN (bar)	Obj. číslo.	Hmotn. (kg)	D (mm)	D1 (mm)	D2 (mm)	D3 (mm)	H max. (mm)	AL	SC
20	15	16	727 700 206	0.216	95	65	28	14	12	4	M12
25	20	16	727 700 207	0.279	105	75	34	14	12	4	M12
32	25	16	727 700 208	0.429	115	85	42	14	16	4	M12
40	32	16	727 700 209	0.621	140	100	51	18	16	4	M16
50	40	16	727 700 210	0.722	150	110	62	18	20	4	M16
63	50	16	727 700 211	0.900	165	125	78	18	20	4	M16
75	65	16	727 700 212	1.110	185	145	92	18	20	4	M16
90	80	16	727 700 313	1.390	200	160	108	18	20	8	M16
110	100	16	727 700 314	1.407	220	180	128	18	20	8	M16
125	100	16	727 700 315	1.408	220	180	135	18	20	8	M16
140	125	16	727 700 716	2.318	250	210	158	18	26	8	M16
160	150	16	727 700 717	3.491	285	240	178	22	26	8	M20
180	150	16	727 700 718	3.108	285	240	188	22	26	8	M20
200	200	16	727 700 719	5.600	340	295	235	22	29	8	M20
225	200	16	727 700 720	5.533	340	295	238	22	29	8	M20
250	250	16	727 700 721	6.632	395	350	288	22	32	12	M20
280	250	16	727 700 722	6.573	395	350	294	22	32	12	M20
315	300	16	727 700 723	7.903	445	400	338	22	36	12	M20
355	350	16	727 700 724	14.587	515	460	376	23	42	16	M20
400	400	16	727 700 725	20.034	574	515	430	26	42	16	M24

Technické údaje jsou nezávazné. Konstrukční a rozměrové změny vyhrazeny.
Platí naše všeobecné obchodní podmínky.

TITAN - METALPLAST s.r.o. / Volgogradská 106 / 460 10 Liberec - Karlínky
telefon: (+420) 483 359 061 / e-mail: obchod@titan-metalplast.cz / www.titan-metalplast.cz